



+44 (0)1482 327944
 Main Street Hull HU2 0LF UK
 Fax +44 (0)1482 216670 sales@fabricast.co.uk



Bright Cold Sized Bar EN 10088-3 1.4404 (316S11 BS970 Part 3 1991)

Diam	Wt Per Mtr	Tolerance	Std Lengths	Diam	Wt Per Mtr	Tolerance	Std Lengths
35mm	7.55	h9	3-3.2 mtrs	2.1/8"	17.95	h9	3-3.2 mtrs
1.1/2"	8.94	h9	3-3.2 mtrs	2.1/4"	20.13	h9	3-3.2 mtrs
40mm	9.86	h9	3-3.2 mtrs	60mm	22.2	h9	3-3.2 mtrs
1.5/8"	10.5	h9	3-3.2 mtrs	2.3/8"	22.44	h9	3-3.2 mtrs
1.3/4"	12.18	h9	3-3.2 mtrs	2.1/2"	24.85	h9	3-3.2 mtrs
45mm	12.48	h9	3-3.2 mtrs	2.5/8"	27.39	h9	3-3.2 mtrs
1.7/8"	13.98	h9	3-3.2 mtrs	2.3/4"	30.07	h9	3-3.2 mtrs
50mm	15.41	h9	3-3.2 mtrs	75mm	34.68	h9	3-3.2 mtrs
2"	15.09	h9	3-3.2 mtrs	3"	35.76	h9	3-3.2 mtrs

Bright Peeled Bar EN 10088-3 1995 (316S11 BS970 Part 3 1991)

Diam	Wt Per Mtr	Tolerance	Std Lengths	Diam	Wt Per Mtr	Tolerance	Std Lengths
3.1/4"	42	K12	3-5 mtrs	6"	143	DIN 1013 +	3-5 mtrs
3.1/2"	48.69	K12	3-5 mtrs	6.1/2"	172	DIN 1013 +	3-5 mtrs
3.3/4"	55.91	K12	3-5 mtrs	7"	199	DIN 1013 +	3-5 mtrs
4"	63.62	DIN 1013 +	3-5 mtrs	7.1/4"	213	DIN 1013 +	3-5 mtrs
4.1/4"	71.8	DIN 1013 +	3-5 mtrs	7.1/2"	229	DIN 1013 +	3-5 mtrs
4.1/2"	80.5	DIN 1013 +	3-5 mtrs	8"	260	DIN 1013 +	3-5 mtrs
4.3/4"	89.7	DIN 1013 +	3-5 mtrs	8.1/2"	294	DIN 1013 +	3-5 mtrs
5"	99.4	DIN 1013 +	3-5 mtrs	9"	330	DIN 1013 +	3-5 mtrs
5.1/4"	112	DIN 1013 +	3-5 mtrs	9.1/2"	367	DIN 1013 +	3-5 mtrs
5.1/2"	120	DIN 1013 +	3-5 mtrs	10"	407	DIN 1013 +	3-5 mtrs

ICB - MMSS - JAN 08 - P14

