



## Bright Cold Sized Bar EN 10088-3 1.4404 (316S11 BS970 Part 3)

Diam	Wt Per Mtr	Tolerance	Std Lengths	Diam	Wt Per Mtr	Tolerance	Std Lengths
1/8"	0.055	h9	3-3.2 mtrs	12mm	0.888	h9	3-3.2 mtrs
3mm	0.062	h9	3-3.2 mtrs	1/2"	0.994	h9	3-3.2 mtrs
5/32"	0.095	h9	3-3.2 mtrs	13mm	1.04	h9	3-3.2 mtrs
4mm	0.099	h9	3-3.2 mtrs	14mm	1.21	h9	3-3.2 mtrs
3/16"	0.14	h9	3-3.2 mtrs	9/16"	1.26	h9	3-3.2 mtrs
5mm	0.154	h9	3-3.2 mtrs	15mm	1.39	h9	3-3.2 mtrs
7/32"	0.188	h9	3-3.2 mtrs	5/8"	1.55	h9	3-3.2 mtrs
6mm	0.222	h9	3-3.2 mtrs	16mm	1.58	h9	3-3.2 mtrs
1/4"	0.248	h9	3-3.2 mtrs	11/16"	1.88	h9	3-3.2 mtrs
7mm	0.302	h9	3-3.2 mtrs	18mm	2	h9	3-3.2 mtrs
5/16"	0.388	h9	3-3.2 mtrs	3/4"	2.24	h9	3-3.2 mtrs
8mm	0.395	h9	3-3.2 mtrs	20mm	2.47	h9	3-3.2 mtrs
9mm	0.499	h9	3-3.2 mtrs	13/16"	2.63	h9	3-3.2 mtrs
3/8"	0.559	h9	3-3.2 mtrs	22mm	2.98	h9	3-3.2 mtrs
10mm	0.617	h9	3-3.2 mtrs	7/8"	3.04	h9	3-3.2 mtrs
11mm	0.746	h9	3-3.2 mtrs	15/16"	3.49	h9	3-3.2 mtrs
7/16"	0.761	h9	3-3.2 mtrs	24mm	3.55	h9	3-3.2 mtrs

## Bright Peeled/Reeled Bar EN 10088-3 1.4404 1995 (316S11 BS970 Part 3)

25mm	3.85	h9	3-3.2 mtrs
1"	3.98	h9	3-3.2 mtrs
26mm	4.17	h9	3-3.2 mtrs
27mm	4.5	h9	3-3.2 mtrs
1.1/8"	5.03	h9	3-3.2 mtrs
30mm	5.55	h9	3-3.2 mtrs
1.1/4"	6.21	h9	3-3.2 mtrs