



Bright Cold Sixed Bar 321S31 BS970 Part 3 1991

Diam	Wt Per Mtr	Tolerance	Std Lengths	Diam	Wt Per Mtr	Tolerance	Std Lengths
5mm	0.154	h9	3-3.2 mtrs	12mm	0.889	h9	3-3.2 mtrs
6mm	0.222	h9	3-3.2 mtrs	1/2"	0.994	h9	3-3.2 mtrs
1/4"	0.249	h9	3-3.2 mtrs	5/8"	1.551	h9	3-3.2 mtrs
5/16"	0.387	h9	3-3.2 mtrs	16mm	1.578	h9	3-3.2 mtrs
8mm	0.398	h9	3-3.2 mtrs	3/4"	2.237	h9	3-3.2 mtrs
3/8"	0.557	h9	3-3.2 mtrs	20mm	2.47	h9	3-3.2 mtrs
10mm	0.62	h9	3-3.2 mtrs	7/8"	3.038	h9	3-3.2 mtrs
7/16"	0.761	h9	3-3.2 mtrs	24mm	3.543	h9	3-3.2 mtrs

Bright Peeled/Reeled 321S31 BS970 Part 3 1991

Diam	Wt Per Mtr	Tolerance	Std Lengths	Diam	Wt Per Mtr	Tolerance	Std Lengths
25mm	3.85	h9	3-3.2 mtrs	1.5/8"	10.5	h9	3-3.2 mtrs
1"	3.98	h9	3-3.2 mtrs	1.3/4"	12.18	h9	3-3.2 mtrs
1.1/8"	5.03	h9	3-3.2 mtrs	1.7/8"	13.98	h9	3-3.2 mtrs
30mm	5.55	h9	3-3.2 mtrs	50mm	15.41	h9	3-3.2 mtrs
1.1/4"	6.21	h9	3-3.2 mtrs	2"	19.9	h9	3-3.2 mtrs
1.3/8"	7.47	h9	3-3.2 mtrs	2.1/4"	2.13	h9	3-3.2 mtrs
1.1/2"	8.94	h9	3-3.2 mtrs	2.1/2"	24.85	h9	3-3.2 mtrs
40mm	9.86	h9	3-3.2 mtrs	2.3/4"	30.07	h9/K12	3-5 mtrs
3"	35.76	h9	3-3.2 mtrs				