



+44 (0)1482 327944  
Main Street Hull HU2 0LF UK  
Fax +44 (0)1482 216670 sales@fabricast.co.uk



**Bright Cold Sized Bar EN 10088-3 1995 (303CU)**

Diam	Kg Per Mtr	Tolerance	Std Lengths
6mm	0.223	h9	3-3.2 mtrs
1/4"	0.249	h9	3-3.2 mtrs
3/8"	0.557	h9	3-3.2 mtrs
10mm	0.62	h9	3-3.2 mtrs
12mm	0.889	h9	3-3.2 mtrs
1/2"	0.994	h9	3-3.2 mtrs
5/8"	1.551	h9	3-3.2 mtrs
16mm	1.578	h9	3-3.2 mtrs
3/4"	2.237	h9	3-3.2 mtrs
20mm	2.47	h9	3-3.2 mtrs
7/8"	3.038	h9	3-3.2 mtrs

**Bright Peeled/Reeled Bar EN 10088-3 1995 (303CU)**

25mm	3.871	h9	3-3.2 mtrs
1"	3.97	h9	3-3.2 mtrs
1.1/8"	5.033	h9	3-3.2 mtrs
30mm	5.548	h9	3-3.2 mtrs
1.1/4"	6.349	h9	3-3.2 mtrs
1.1/2"	8.951	h9	3-3.2 mtrs
2"	15.906	h9	3-3.2 mtrs

ICB - MMSS - JAN 08 - P12

