



## Bright Bar 431S29 BS970 Part 3 1991

Diam	Wt Per Mtr	Tolerance	Std Lengths	Diam	Wt Per Mtr	Tolerance	Std Lengths
6mm	0.222	h9	3-3.2 mtrs	9/16"	1.26	h9	3-3.2 mtrs
1/4"	0.248	h9	3-3.2 mtrs	15mm	1.39	h9	3-3.2 mtrs
5/16"	0.388	h9	3-3.2 mtrs	5/8"	1.55	h9	3-3.2 mtrs
8mm	0.395	h9	3-3.2 mtrs	16mm	1.58	h9	3-3.2 mtrs
3/8"	0.559	h9	3-3.2 mtrs	11/16"	1.88	h9	3-3.2 mtrs
10mm	0.617	h9	3-3.2 mtrs	3/4"	2.24	h9	3-3.2 mtrs
7/16"	0.761	h9	3-3.2 mtrs	20mm	2.47	h9	3-3.2 mtrs
12mm	0.888	h9	3-3.2 mtrs	7/8"	3.04	h9	3-3.2 mtrs
1/2"	0.994	h9	3-3.2 mtrs	24mm	3.55	h9	3-3.2 mtrs

## Bright One Pass Ground Bar 431S29 BS970 Part 3 1991

Diam	Wt Per Mtr	Tolerance	Std Lengths	Diam	Wt Per Mtr	Tolerance	Std Lengths
25mm	3.85	h9	3-3.2 mtrs	1.3/4"	12.41	h9	3-3.2 mtrs
1"	3.98	h9	3-3.2 mtrs	50mm	15.41	h9	3-3.2 mtrs
1.1/8"	5.03	h9	3-3.2 mtrs	2"	15.9	h9	3-3.2 mtrs
30mm	5.55	h9	3-3.2 mtrs	2.1/4"	20.13	h9	3-3.2 mtrs
1.1/4"	6.21	h9	3-3.2 mtrs	60mm	22.2	h9	3-3.2 mtrs
1.3/8"	7.47	h9	3-3.2 mtrs	2.3/8"	22.44	h9	3-3.2 mtrs
35mm	7.55	h9	3-3.2 mtrs	2.1/2"	24.85	h9	3-3.2 mtrs
1.1/2"	8.94	h9	3-3.2 mtrs	2.5/8"	27.39	h9	3-3.2 mtrs
40mm	9.86	h9	3-3.2 mtrs	2.3/4"	30.07	h9	3-3.2 mtrs
1.5/8"	10.5	h9	3-3.2 mtrs	3"	35.76	h9/K12	3-5 mtrs

## Bright Peeled/Turned Bar 431S29 BS970 Part 3 1991

Diam	Wt Per Mtr	Tolerance	Std Lengths	Diam	Wt Per Mtr	Tolerance	Std Lengths
3.1/4"	42	K12	3-5 mtrs	5.1/4"	112	DIN 1013 +	3-5 mtrs
3.3/4"	55.91	K12	3-5 mtrs	5.1/2"	120	DIN 1013 +	3-5 mtrs
4"	63.62	DIN 1013 +	3-5 mtrs	6"	143	DIN 1013 +	3-5 mtrs
5"	99.4	DIN 1013 +	3-5 mtrs	6.1/2"	172	DIN 1013 +	3-5 mtrs